

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

13
23

History of original corner establishment:

Corner established in 1884 by Henry W. Cooke under General Land Office contract #494

Surveyor General record states;

Set post with marked stone for $\frac{1}{4}$ sec.cor. from which;

A Pine 50 ins. diam. bears N15E, 31 lks.

A Pine 20 ins. diam. bears S20W, 41 lks.

DIAGRAM

T 16S R32E

S 31

$\frac{1}{4}$

S 6

T17S R32E

No record of subsequent remonumentation was found in the County records

Description of corner evidence found:

Found marked stone in mound of stone and 2 BTs

See map of survey dated October 1981

Description of monument and accessories I established to perpetuate the original location of this corner:

In place of stone I set a $2\frac{1}{2}$ x 30 inch aluminum pipe with aluminum cap marked as shown 20 inches in the ground from which;

ORIGINAL BTs

A 22 inch P.Pine bears S21W, 27.4 feet, live, not vigorous, scribes visible
A 50 inch+ P.Pine bears N20W, 20 feet+, dead and down on face, did not roll it

NEW BTs

A 24 inch P.Pine bears S48W, 39.3 feet, marked $\frac{1}{4}$ S6 BT
A 10 inch red fir bears N20W, 5.6 feet, marked $\frac{1}{4}$ S31 BT

Buried stone East and alongside of pipe

Raised mound of stone

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 10, 1964
DUANE I. GRIFFITH
644

T16S R32E

S 31

$\frac{1}{4}$

S 6

T17S

1981

OPLS 644

Date October 6, 1981 . . .

Brass washer nailed to BT blaze. Used steel tape and magnetic compass with 21° East declination in the establishment of accessories. Original BTs measured to face of blaze. New BTs measured to center of tree.

Office of Surveyor County of Grant

State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 23 day of Dec, 1981

Robert L. B. 301 by _____
(COUNTY OFFICIAL) (DEPUTY)