


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Not previously established.



H-9

Description of corner evidence found:

None.

S-E wire fence corner bears South 55° East, 36 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

At calculated position as determined by traverse swing tie, set a 2 1/2 inch O.D. x 30 inch long aluminum pipe 24 inches in ground with 3 1/4 inch aluminum cap marked as shown:

Marked 2 new bearing trees:


a 6" dbh Ponderosa Pine bears North 62° East, 27.1 ft., scribed "S1/16S9BT";

a 5" dbh Ponderosa Pine bears North 26°45' West, 36.6 ft., scribed "S1/16S8BT".

Nailed brass washer marked "AS&E LS 1026" in lower blaze.

Raised a mound of stones and earth 2 foot diameter base to top of cap.

Painted a 6" red band and faces red and nailed signs 54-3 and 54-9 on all BT's. Set steel post with sign 54-9 6 feet East of and facing corner and sign 54-2 and set steel post with sign 54-2 6 feet South of corner.



Magnetic Declination 20°E

I hereby certify the above corner monument was established as herein described on September 20, 1983.

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 28 day of Dec, 1983
Robert D. Gayett by David B. Armstrong
(COUNTY OFFICIAL) (DEPUTY)

