


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1884 by Henry W. Cooke under General Land Office Contract 494. Surveyor Generals records stat: Set a basalt stone 16x16x10 in. 1110 in. in ground for 1/2 section corner marked 1/4 on W face. From which a fir 26 in. dia. side. bears N20° E 44 lks dist. marked 1/4 S BT. A fir 30 in. dia. bears N10° W 8 lks dist. marked 1/4 S BT.



Description of corner evidence found:

No evidence of original stone found. Found 24" pine stump with scribing visible. Found a 30" pine stump with scribing visible. It is found that the bearings and distance of record are reversed. i.e. record N20° E 44 lks should actually read N44° E 20 lks & record, N10° W 8 lks, should read N80° W 10 lks. Positioned corner at S50° W, 14.0 ft. & S80° E, 6.6 ft. from the said tree stumps, as the best overall fit on the trees. Note: Record calls for fir trees, there are no fir trees in the area, the scribing is recognizable as being Cooke's.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with 3 1/2" aluminum cap, stamped as shown in diagram. Set 20" in ground, placed a ring of stone around pipe. From Which: A pine 8" dia. bears N38° W 40.3 ft. scribed 1/4 S13 BT. A pine 9" dia. bears N41° E 55.1 ft. Scribed 1/4 S13 BT. Nailed brass washers stamped PLS 848, bearing tree & warning signs to each tree. Painted 6" red band around each tree. Placed steel posts with boundry & warning sigs approx. 5.0 ft. south & 5.0 ft. west.



Corner monumented 8-9-82
Witnessed by D. Mitchell Ferguson

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 17 day of Feb, 1983
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)