

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1884 by Henry W Cooke, under General Land Office Contract 494. Surveyor Generals Records State: Set post 3½ft. long 3 inches square with marked stone 122 inches in ground for ¼ section corner, marked ¼S on North face, dug pits 18 x 18 x 12 inches east and west of corner. 5½ ft. dist and raised a mound of earth 2ft. high 3½ft. base around post.

DIAGRAM

T16S R33½E
11S16
42S21
1982
PLS 848

Description of corner evidence found:

No evidence found corner position falls on North edge of road.

From which

No evidence of pits found.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 30" x 2" aluminum pipe with 3½" aluminum cap, stamped as shown in the diagram, set 14" in the ground and raised a mound of stone around the pipe.

From which

Set steel posts with bearing Tree and warning signs.

North, 5.4ft. and South 5.4ft. from cor.

No Bearing Trees available.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 7-16-82
Witnessed by D. Mitchell Ferguson

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 17 day of Feb, 1983
Robert D. Baggett by
(COUNTY OFFICIAL) (DEPUTY)