

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.

DIAGRAM

T16S R33½E
C $\frac{W \frac{1}{16}}{S21}$ C
1982
PLS 848

Description of corner evidence found:

Corner not previously established.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 30" x 2" aluminum pipe with 3½" aluminum cap, stamped as shown on the diagram, set 22" in the ground.

From which

A pine 10" dia. Bears N 4°W, 15.4ft. scribed C W 1/16 S21 BT

A pine 8" dia. Bears S 8°W, 6.7ft. scribed C W 1/16 S21 BT

Nailed brass washers stamped PLS 848, Bearing Tree signs and warning signs to each Bearing Tree and painted a red band around each tree.

Set steel posts with warning and boundary signs, 4'S and 3'W.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 8-2-82
Witnessed by D. Mitchell Ferguson

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 17 day of Feb, 1983
Robert D. Bazzett by _____
(COUNTY OFFICIAL) (DEPUTY)