

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1884 by Hevry W. Cooke, under General Land Office Contract 494. Surveyor Generals Records state: Set Basalt stone 16 x 14 x 10 inches 11 inches in ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on W face, dug pits 18 x 18 x 12 inches north and south of corner, 5 $\frac{1}{2}$ ft. dist. and raised a mound of earth 2ft. high 3 $\frac{1}{2}$ ft. base alongside.

DIAGRAM

T16S R33 $\frac{1}{2}$ E
 $\frac{1}{4}$
S21 S22
1982
PLS 848

Description of corner evidence found:

No stones of record size in serarch area or in fence line 100ft. east.

From which

No traces of the pits, set corner position by proportion.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 30" x 2" aluminum pipe with 3 $\frac{1}{2}$ " aluminum cap, stamped as shown on the diagram, set 20" in the ground.

From which

Set steel posts with warning and Bearing Tree signs.

East 5.5ft. and West 5.1ft.

No Bearing Trees available.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 8-82
Witnessed by D. Mitchell Ferguson

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 17 day of Feb, 1983
Robert D. Right by _____
(COUNTY OFFICIAL) (DEPUTY)