

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1884 by Henry W. Cook, under General Land Office Contract No. 494.

SurveyorsGenerals Records state:

Set basalt stone 16x12x10 in., marked $\frac{1}{2}$ on the west face.

Dug pits 18x18x12 in. N&S of stone, $5\frac{1}{2}$ ft. dist. and raised a mound of earth 2 ft. high $3\frac{1}{2}$ ft. base alongside.

DIAGRAM

T16S R33 $\frac{1}{2}$ E
S22 S23
1982
PLS848

Description of corner evidence found:

Found 16x11x9 in. stone lying flat in a circle of stone.
When stone is set upright, $\frac{1}{2}$ is on north face.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with $3\frac{1}{2}$ " aluminum cap, stamped as shown in the diagram.
Set 20" in the ground, placed original stone alongside pipe & raised a ring of stone around pipe.

From Which?

Set steel posts with warning & bearing tree signs, East 5.0 ft. & West 5.0 ft.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 9-82
Witnessed by D. Mitchell Ferguson

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 17 day of Feb, 1983
Robert D. Leggett by _____
(COUNTY OFFICIAL) (DEPUTY)