

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1884 by Henry W. Cooke, under General Land Office Contract 494. Surveyor Generals Records state: Set post 3½ft. long 3 inches square with marked stone 24 ins. in ground from ¼ section corner marked ¼ on N face, dug pits 18 x 18 x 12 ins. East and West of corner 5½ft. dist. and raised mound of earth 2ft. high 3½ft base around post.

DIAGRAM

T16S R33½E
¼ S21
S28
1982
PLS 848

Description of corner evidence found:

No evidence found.

No traces of pits found, set corner by proportion.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 30" x 2" aluminum pipe with 3½" aluminum cap, stamped as shown on the diagram, set 28" in the ground.

From which

A pine 29" dia. Bears N 68½°E, 16.6ft. scribed ¼ S21 BT

A pine 29" dia. Bears S 20° 40'E, 98.7ft scribed ¼ S28 BT

Nailed brass washers stamped PLS 848, Bearing Tree signs and warning signs to each tree, painted a 6" red band around each tree

Set steel post with warning and boundary signs 5'N and 5'S from corner;

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 7-21-82
Witnessed by D. Mitchell Ferguson

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 7 day of Feb, 1983
Clarence Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)