

19

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1884 by Heney W. Cooke, under General Land Office Contract 494, Surveyor Generals Records state; Set post 4½ft. long 4 inches square with marked stone 12 ins. in ground, for corner to sections 21, 22, 27, and 28, marked T16S R22 on NE, R33½E S27 on SE, S28 on SW and S21 on NW faces, with 2 notches on south and 3 notches on east edges. Dug pits 18 x 18 x 12 inches in each section, 5½ft. dist. and raised a mound of earth 2ft. high 4½ft. base around post.

DIAGRAM

T16S R33½E
 S21 | S22
 S28 | S27
 1982
 PLS 848

Description of corner evidence found:


No evidence found, falls in cultivated field.

No trees originally established.
 Calls to corner west and south no help, as they have meandered due to old beaver work.
 Set corner by proportion.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 30" x 2" aluminum pipe with 3½" aluminum cap, stamped as shown on the diagram, set 22" in the ground.

From which
 Steel posts with Bearing Tree, warning and boundary signs, bear north 5.0ft., east 3.7ft., south 4.9ft. and west 4.8ft. (Boundary signs, north and east only)
 No trees available.



Corner monumented 7-23-82
 Witnessed by D. Mitchell Ferguson

Office of Sumner County of Grant
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 7 day of Feb, 1983
Robert D. Baggett by _____
 (COUNTY OFFICIAL) (DEPUTY)