

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1884 by Henry W. Cooke, under Federal Land office Contract 494. Surveyor Generals Records state: Set basalt stone 16" x 12" x 7", 11 inches in the ground for $\frac{1}{4}$ section corner marked $\frac{1}{4}$ on north face. Dug pits 18 x 18 x 12 inches east and west of corner $5\frac{1}{2}$ ft. dist. and raised a mound of earth $1\frac{1}{2}$ ft. high $3\frac{1}{2}$ ft. base alongside.

DIAGRAM

T16S R33 $\frac{1}{2}$ E

$\frac{1}{4}$ S22
S27

1982
PLS 848

Description of corner evidence found:

Found 16" x 10" x 6" stone with $\frac{1}{4}$ on face, lying loose in cultivated ground. Stone has been moved around over the years by farming equipment.

No traces of pits or mound.

I could not accept the position of the stone as the $\frac{1}{4}$ corner position, therefore $\frac{1}{4}$ corner is set by proportion, falling 40 ft. west of where stone was found.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 30" x 2" aluminum pipe with 3 $\frac{1}{2}$ " aluminum cap, stamped as shown on the diagram, set 24" in the ground. Placed original stone north alongside and set 12" x 12" x 10" stone north alongside pipe.

From which

Set steel posts with Bearing Tree and warning signs.

Norht 4.5 ft. and south 4.8 ft.

No trees available.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON

JULY 12, 1968

DOUGLAS M. FERGUSON
848

Corner monumented 8-8-82

Witnessed by D. Mitchell Ferguson

Office of Surveyor County of Grant
State of Oregon I hereby certify that the within instrument was filed in this office
for record on the 17 day of Feb, 1983
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)