

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1884 by Henry W. Cooke, under General Land Office Contract 494. Surveyor Generals Records state: Set basalt stone 18 x 16 x 6 ins., 12 ins. in ground for $\frac{1}{4}$ section corner marked $\frac{1}{4}$ on W face, f

From which

A pine 12" dia. Bears S 88°E 25 links dist. marked $\frac{1}{4}$ S BT
A pine 36" dia. Bears S 45°W 48 links dist. marked $\frac{1}{4}$ S BT

DIAGRAM

T16S R33 $\frac{1}{2}$ E
 $\frac{1}{4}$
S29 $\frac{1}{2}$ S28
1982
PLS 848

Description of corner evidence found:

Found 18 x 16 x 16 stone, set in ground with $\frac{1}{4}$ on west face.

From which

A pine stump 24" dia. BT scribing visible Bears S 45°W 31.5ft.
A pine 18" dia healed over blazes, bears S 88°E 17ft.
Accepted stone as $\frac{1}{4}$ corner position.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 30" x 2" aluminum pipe with 3 $\frac{1}{2}$ " aluminum cap, stamped as shown on the diagram, set 15" in the ground and raised a mound of stone around the pipe.
Set original stone west alongside pipe.

From which

A pine 12" dia. Bears N 70°E 12.7ft. scribed $\frac{1}{4}$ S28 BT
A pine 9" dia. Bears S 77°W 27.1ft. scribed $\frac{1}{4}$ S 29 BT
Nailed brass washers stamped PLS 848, Bearing Tree signs and warning signs to each tree, painted a 6" red band around each tree.
Set a steel post with warning signs 5' north.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 8-2-82
Witnessed by D. Mitchell Ferguson

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 7 day of Feb, 1983
Robert D. Bugger
(COUNTY OFFICIAL) (DEPUTY)