

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1883 by Henry W. Cooke, under General Land Office Contract 488. Surveyor Generals records state: Set a basalt stone 20x12x10 in. 15 inches in ground for corner to sections 4,5,32,&33 marked with 4 notches on E and 2 notches on W edges.

From Which:

A fir 50 in. dia. bears N70°E 40 lks dist. marked T16S R33½E S33 BT.

A pine 24 in. dia. bears S15°E 69 lks dist. marked T17S R33½E S4 BT.

A pine 36 in. dia. bears S28°W 23 lks dist. marked T17S R33½E S5 BT.

A pine 16 in. dia. bears N45°W 54 lks dist. marked T16S R33½E S32 BT.

DIAGRAM

T16S		R33½E
S32		S33
S5		S4
1982		
PLS848		

Description of corner evidence found:

Found 18"x9"x8" stone with 2 grooves on west face & 4 grooves on east face set in ground.

From Which:

A fir 42" dia. bears N80°E 27.6 ft.

A pine 22" dia. bears N52°W 36.1 ft.

A pine 24" dia. bears S20°W 16.6 ft.

A pine 22" dia. bears S15°E 47.5 ft.

Trees verify position of stone.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 30"x2" aluminum pipe with 3½" aluminum cap, stamped as shown in diagram. Set 20" in ground. Placed original stone east alongside.

From Which:

A fir 12" dia. bears N59°W 14.2 ft. scribed T16S R33½E S32 BT.

A fir 11" dia. bears N32°E 15.8 ft. scribed T16S R33½E S33 BT.

A fir 15" dia. bears S87°W 11.6 ft. scribed T16S R33½E S5 BT.

Nailed brass washers stamped PLS848, with warning & BT signs to each tree, and painted 6" red band around each tree.

Set steel post with warning sign 2 ft. north.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 7-30-82
Witnessed by D. Mitchell Ferguson

Office of Sumner County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 17 day of Feb, 1983
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)