

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1883 by Henry W. Cooke, under General Land Office Contract 488. Surveyor Generals records state: Set a basalt stone 18x16x5 in. 12 in. in ground for $\frac{1}{4}$ Sec. corner. Marked $\frac{1}{4}$ on N face

From Which:

A pine 8 in. bears N 50° E 17 lks dist. marked $\frac{1}{4}$ S B.T.
A pine 6 in. bears S 40° E 11 lks dist. marked $\frac{1}{4}$ S B.T.

DIAGRAM

T16S R33 $\frac{1}{2}$ E
S33
 $\frac{1}{4}$ — 54 —
T17S
1982
PLS848

Description of corner evidence found:

No evidence of bearing trees found, due to logging activity.
Corner set by proportion.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3 $\frac{1}{2}$ in. aluminum cap.
Stamped as shown in diagram. Set 26" in ground.

From Which:

A fir 12" dia. bears N 43° W 6 $\frac{3}{4}$ ft. scribed $\frac{1}{4}$ S 33 B.T.
A pine 17" dia. bears S 43° E 15 $\frac{1}{2}$ ft. scribed $\frac{1}{4}$ S 4 B.T.

Nailed brass washers stamped PLS 848, warning signs & bearing tree signs to each tree.

Painted 6" red band around each tree. Set steel post with warning sign 2 ft. north.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1988
DOUGLAS M. FERGUSON
848

Corner monumented 9-82
Witnessed by D. Mitchell Ferguson

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 17 day of Feb, 1983
Robert D. Bisset by _____
(COUNTY OFFICIAL) (DEPUTY)