

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Henery W. Cooke, Under General Land Office Contract No. 422. Surveyor Generals Notes State: Set a basalt stone 14x12x10" 10" in the ground for 1/4 section corner marked 1/4 on N face and raised a mound of stone alongside.



Description of corner evidence found:

Found a 14"x12"x8" stone set 5" in the ground, with a mound of stone around pipe. No accessories originally established. Accepted stone as 1/4 corner position.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3 1/2" aluminum cap stamped as shown in diagram. Set 14" in the ground, set original stone West alongside pipe & raised a mound of stone around pipe.

From Which:

A Juniper 10" dia. bears S72°E, 87.1 ft. scribed 1/4 S12 BT.

A " 12" " " N20°W, 124.2 ft. " " S1 BT.

Set steel post with warning sign West 5 ft.

Nailed brass washers stamped PLS848, bearing tree & warning signs to each tree.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Corner monumented 6-29-83

Witnessed by D. Mitchell Ferguson

**OREGON
JULY 12, 1988
DOUGLAS M. FERGUSON
848**

Office of.....Surveyor..... County of.....Grant.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office

for record on the..29th day of.....August....., 19..83.

Robert D. Bayne by
(COUNTY OFFICIAL) (DEPUTY)