


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Henry W. Cooke, Under General Land Office Contact No. 422. Surveyor Generals Notes State: Set a basalt stone 18x11x7" 12" in the ground for corner, marked 1/4 on W face and raised a mound of stone alongside.



Description of corner evidence found:

No evidence found, fenceing activity through the area has destroyed all traces.
No accessories originally established. Set corner position by proportion.

Description of monument and accessories established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3 1/2" aluminum cap stamped as shown in diagram. Set 12" in ground & raised a mound of stone & earth around pipe.
From Which:
A Juniper 7" dia. bears S60°E, 43.3 ft. scribed 1/4 S13 BT.
A " 6" " " S42°W, 17.6 ft. " " S14 BT.
Set a steel post with warning & boundry signs 10' North.
Nailed brass washers stamped PLS848, bearing tree & warning signs to each tree.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson
OREGON
JULY 12, 1958
DOUGLAS M. FERGUSON
848

Corner monumented 7-3-83
Witnessed by D. Mitchell Ferguson

Office of.....Surveyor..... County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 29th day of.....August....., 1983.
Robert D. Baggett by
(COUNTY OFFICIAL) (DEPUTY)