CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original survey by Henry W. Cooke in 1884.
Set: 16X14X12 basalt stone, 11" in ground, marked CC, 3 notches on E and W edges.
BT's: 40" fir, N10° E, 50 links=33.00'
8" fir, S44° E, 61 links=40.26'
20" fir, S40° W, 60 links=39.60'

DIAGRAM



Description of corner evidence found:

Found original stone, 18X14X12 with marks faint on North, South and CC faint on East side. Marks not on proper sides, but stone is upright and solid.
The following Bearing Trees were found:
(40") large burned pine snag 33' to face, N01° W
13" Lodgepole pine, S38½° E, 40.0' to face, scribed "S R34E S3 BT"
25" fir stump S34° W, 40.3', face partially visible and some scribing.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2½"X30" alum. pipe with alum. cap 24" in ground in a stone mound.
Buried orig. stone flush with ground North of pipe. The following BT's marked:
10" white fir, S58½° W, 34.1' to face, 34.5' to CL, mkd:"CCT16SR34ES4BT"
11" Lodgepole pine, S61° E, 28.7' to CL, 28.2' to face, mkd:"CCT16SR34ES3BT"
Above trees have painted red faces and bands, USFS signs and brass washers with LS 1658 stamped on them attached to lower portion of face.
Variation 17½° East by staff compass.
Witnessed by Randall Schulson, Aug. 1983.

REGISTERED PROFESSIONAL LAND SURVEYOR
Ronald H. Schulson
OREGON
JULY 14, 1978
RONALD H. SCHULSON
1658

Alum. cap stamped as shown:



Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 30 day of Nov, 19 83
Roberta A. Bergstrom by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO—798-276

A-13