CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original survey by Henry W. Cooke in 1884.
Set: Basalt stone, 24X16X12, 18" in ground, with 5 notches on South & 3 notches on East edge
BT's: 14" pine N50°E, 20 links=13.2'
24" pine S67°E, 12 links=7.92'
48" pine S15°W, 67 links=44.22'
18" pine N10°W, 32 links=21.12'



Description of corner evidence found:

Found original 24X12X11 stone with 5 notches on West. & 3 NOTCHES ON EAST. Also found the following bearing trees:
15" p. pine, N43½°E, 13.1' to CL, almost closed face.
20" p. pine snag, S72°E, 7.9' to CL, scribe showing but almost unreadable.
36" p. pine uproot, S06°W, 45.7'±, scribe showing.
21" p. pine, N7¼°W, 21.4' to CL, open with some Scribing visible "S4"

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2½"X30" alum. pipe with alum. cap 20" in ground in stone mound. Buried original stone flat along North side of pipe. From which the following new Bearing Trees bear:
12" p. pine, S43 3/4°W, 93.9' to face, 94.4' to CL, Mkd:"T16SR34ES9BT"
9" p. pine, S78 3/4°E, 37.9' to face, 38.2' to CL, Mkd:"T16SR34ES10BT"
The above trees have painted red faces and red bands, USFS signs and a Brass washer stamped LS 1658 attached to lower portion of face.
Variation 17° East using staff compass.
Witnessed by Randall Schulson, Aug. 1983.

Alum. cap stamped as shown:

REGISTERED PROFESSIONAL LAND SURVEYOR
Ronald H. Schulson
OREGON
JULY 14, 1978
RONALD H. SCHULSON
1658

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 30 day of NOV, 19 83
Robert D. Boyd by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

E-13