# CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**History of original corner establishment:**

Corner established by Henry Cooke under
Contract No. 488, dated 1883
Set a stone 18x16x14, marked 2 notches on S
and 1 notch on E edges.
16" Tamarack N 52° E 48 lks
48" Pine S 42° E 42 lks
10" Pine S 15° W 26 lks
30" Fir N 5° W 67 lks

**DIAGRAM**

T16S R34E

| | |
|---|---|
| 23 | 24 |
| 26 | 25 |

**Description of corner evidence found:**

Stone 18x16x14
22" Tamarack N 52° E 48 lks with scribe T16S R visible
48" Pine S 42° E 42 lks, face healed over, axe work visible in bark

**Description of monument and accessories I established to perpetuate the original location of this corner:**

I replaced the stone with a 2"x30" Alum. pipe with 3½" cap set in stone mound and stamped:
10" Tamarack bears N 15° W 20.3', scribed T16S R34E S 23 BT
15" Fir bears S 9° E 22.3', scribed T16S R34E S 26 BT
Each BT has a brass disc (LS 559), BT tag, sign 54-4

T16S R34E
S23 | S24
S26 | S25
1981
RLS 559

I certify the corner was restored as described Sept. 9, 1981

Witness: Sherm Zemke
Sherm Zemke

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Elbert Driver
OREGON
JANUARY 2, 1962
ELBERT DRIVER
559

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 21 day of Oct, 1981
Robert D Bagett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO 799-509

R-21