CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Henry Cooke under
Contract No. 488, dated 1883
Set a stone 14x12x6 marked ¼ on W face
40" Pine S 85° W 30 lks
24" Tamarack S 68° E 39 lks

DIAGRAM

T16S R34E

¼

26 | 25

Description of corner evidence found:

Found stone 15x9x6 firmly set with ¼ chisled on top
30" Pine S 85° W 30 lks, face healed over, did not open
13" Tamarack S 68° E 39 lks, scribe ¼ S BT visible

Description of monument and accessories I established to perpetuate the original location of this corner:

I replaced the stone with a 2"x30" Alum. pipe with 3½" cap in stone mound with the original stone buried along South side of pipe and stamped:
6" Fir bears S 17° W 15.0', scribed ¼ S 26 BT
6" Fir bears S 21° E 17.8', scribed ¼ S 25 BT
Each BT has a brass disc (LS 559), BT tag, sign 54-4

T16S R34E
¼
S26 | S25
1981
RLS 559

I certify the corner was restored as described Sept. 8, 1981

Witness: Sherm Zemke
Sherm Zemke

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Elbert Driver
OREGON
JANUARY 2, 1962
ELBERT DRIVER
559

Office of Surveyor *County of* Grant
State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 21 *day of* Oct, 19 81
Robert D Baggett *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO 799-509

T-21