CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Corner established in 1881 by Henery W. Cooke, Under Gemeral Land Office Contract No. 422. Surveyor Ganerals Notes State:
Set basalt stone 14x11x11" 10" in the ground, for the ¼ corner marked ¼ on W face. From which:
A Pine 60" dia. bears N17°E, 65 lks dist. marked ¼ S BT.
A " 54" " " N78°W, 78 " " " " " ".

DIAGRAM

T16S R36E
S3 ¼ S2
1983
PLS848

Description of corner evidence found:

No evidence of stone found, corner falls in old skid trail.
Found a Pine stump, scribed ¼ S BT, set corner at record S78°E, 51.5 ft. An old rotten Pine bears N39°E, 42.9 ft. from corner position.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30"x2" aluminu mpipe with a 3½" aluminum cap stamped as shown in diagram.
Set 26" in the ground.
From which:
A Pine 9" dia. bears N15°E, 15.8 ft. scribed ¼ S2 BT.
A " 10" " " S38°W, 13.5 ft. " " S3 " .
Set steel post with warning sign N30°E, 4 ft.
Nailed brass washers stamped PLS848, bearing tree & warning signs to each tree.

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 7-5-83
Witnessed by Jeff Smith

Office of.....Surveyor..... *County of*.....Grant.....
State of.....Oregon....., *I hereby certify that the within instrument was filed in this office for record on the*..29th*day of*.....August....., *19*....83.
.....Robert H. Bruyere..... *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

GPO—798-276

C-17