CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Henry W. Cooke, Under General Land Office Contract No. 422. Surveyor Generals Notes State:
Set basalt stone 14 x 12 x 7 ins. 10 ins. in ground for ¼ sec. cor. marked ¼ on N face.
From which:
A Pine 16 ins dia. bears S 15°W, 17 lks. dist. marked ¼ S BT.
A Pine 12 ins. dia. bears N 80°W, 63 liks. dist. marked ¼ S BT/

DIAGRAM

T16S R36E

¼S2
¼S11

1983
PLS 848

Description of corner evidence found:

Found 15" x 13" x 6" stone with marks bisible (can't make out ¼ stone in rough) on North face, set 8" in the ground.
From Which:
A Pine 20" dia. live in good condition with healed over upper & lower blazes, bears S37°E, 11.2 ft.
A Pine 20" dia. live in good condition with scribing visible, bears N73°W, 41.6 ft.
Accepted position of the stone as ¼ cor. position.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" x 2" aluminum pipe with a 3½" aluminum cap stamped as shown in diagram.
Set 22" in the ground & set original stone West alongside pipe.
From which:
A Pine 20" dia. (an original bearing tree) bears S37°E, 11.2 ft. new scribing reads, ¼ S11 BT.
A Pine 20" dia. (an original bearing tree) bears N73°W, 41.6 ft. new scribing reads, ¼ S2 BT.
Set a steel post with warning sign North 5 ft.
Nailed brass washers stamped PLS 848, bearing tree & warning signs to each tree.

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Date June 14, 1983

Witnessed by D. Mitchell Ferguson

Office of.....Surveyor..... *County of*.....Grant.....
State of...Oregon..... *, I hereby certify that the within instrument was filed in this office for record on the*.....29th..... *day of*.....August..... *, 19*83.
.....Lorlen T. D. Bagett..... *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

E-19