CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Henery W. Cooke, Under General Land Office Contract No.422. Surveyor Generals Notes State: Set a basalt stone 16x14x12" 11" in the ground for corner to sections 1, 2, 11, & 12 marked with 5 notches on S and 1 notch on E edges and raised a mound of stone 3 ft. high 4½ ft. base alongside.

DIAGRAM

T16S R36E
S2 | S1
S11 | S12
1983
PLS848

Description of corner evidence found:

Found a 18"x13"x9" stone with 5 grooves on face lying loose in a pile of posts stones & fenceing material.
No accessories originally established. The stone has been displaced by fenceing. Falls approx. 50 ft. West from proportion position & East from N-S fence line. Accepted proportion from ½ mile N, S, E, & W as corner position.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3½" aluminum cap stamped ashown in diagram.
Set 28" in ground, set original stone North alongside.
From which:
A Pine 14" dia. bears N16°33'W, 62.6 ft. scribed T16S R36E S2 BT.
A " 12" " " N34°E, 80.1 ft. " " " S1 "
A " 14" " " S54°27'E, 60.9 ft. " " " S12"
A " 18" " " S33°05'W, 37.1 ft. " " " S11"
Set steel post with warning & boundry signs North 5 ft.
Nailed brass washers stamped PLS848, bearing tree & warning signs to each tree.

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 9-1-83

Witnessed by D. Mitchell Ferguson

Office of.....Surveyor..... *County of*.....Grant.....
State of...Oregon....., *I hereby certify that the within instrument was filed in this office for record on the*29th. *day of*.....August....., *19*..83.
.....Robert O. Bagen..... *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276