CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Henery W. Cooke, Under General Land Office Contract No. 422. Surveyor Generals Notes State: Set a basalt stone 24x14x6" 18" in the ground for ¼ section corner marked ¼ om W face. From which:
A Pine 10" dia. bears S50°E, 25 lks dist. marked ¼ S BT.
A Pine 8" dia. bears S70°W, 50 lks dist. marked ¼ S BT.

DIAGRAM

T16S R36E
¼
S11 | S12
1983
PLS848

Description of corner evidence found:

No traces found of original stone.
Found a Pine 18" dia. live in good condition with ¼ S scribing visible.
Set corner at record N50°W, 16.5 ft. from blaze face. Found a Pine 20" dia. live in good condition with blaze healed over, bears S70°W, 30.1 ft. from accepted corner position. (record dist. was probably slope chained, 33.0 ft.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3½" aluminum cap stamped as shown in diagram.
Set 24" in the ground.
From which:
A Pine 18" dia. (an original bearing tree) bears S50°E, 16.8 ft. new scribimg reads ¼ S12 BT.
A " 8" " "" " " " " S70°W, 30.1 ft. " " " " S11 BT.
Set steel post with warning sign 5 ft. North.
Nailed brass washers stamped PLS848, bearing tree & warning signsto each tree.

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 6-29-83

Witnessed by D. Mitchell Ferguson

Office of.....Surveyor..... *County of*.....Grant.....
State of.....Oregon....., *I hereby certify that the within instrument was filed in this office for record on the*.....29th *day of*.....August....., *19*.....83.
.....Robert L. Bayer..... *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

GPO—798-276

G-21