CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Henery W. Cooke, Under General Land Office Contract No. 422. Surveo Generals Notes State: Set a basalt stone 24x14x10" 18" in the ground for corner to sections 13,14,23, & 24 marked with 3 notches on S & 1 notch on E edges.
From Which:
A Aspen 10" dia. bears N88°W,75 lks dist. marked T16S R36E S13 BT.
No other trees within limits and raised a mound of stone alongside.

DIAGRAM

T16S R36E
S14 | S13
S23 | S24
1983
PLS848

Description of corner evidence found:

Found a 24"x12"x10" stone loose in fence rock jack with 3 grooves on South & 1 groove on East faces.
Foun the remains of an Aspen tree, N88°E, approx. 50 ft. from stone. Therefor the position of the stone is accepted as the corner position.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3½" aluminum cap stamped as shown in diagram. Set 16" in ground, set original stone West alongside pipe & raised a mound of stone around pipe.
From Which:
A Juniper 12" dia. bears N2°W, 42.2 ft. scribed T16S R36E S14 BT.
A " 10" " " N86°E, 5.1 ft. " " " S13 BT.
A " 8" " " S88°E, 40.9 ft. " " " S24 BT.
A Pine 14" " " S85°W, 46.4 ft. " " " S23 BT.
Set steel post with warng sign 5 ft. North.
Nailed brass washers stamped PLS848, Bearing tree & warning signs to each tree.

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner Monumented 7-3-83

Witnessed by Ken Delano

Office of.....Surveyor..... *County of*.....Grant.....
State of.....Oregon....., *I hereby certify that the within instrument was filed in this office for record on the*..29th *day of*.....August....., *19*..83.
.....Robert D. Baggett *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

GPO—798-276

N-21