

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

GLO, 1882, by Henry W. Cooke, contract #427.
 Set 16"x12"x10" Basalt stone with 5 notches on south and 1 notch on east, 11" in ground.
 Mound of stone 4 1/2' base 4' high along side.
 Ravine course South, 2 chains East.
 Top of rocky bluff, 50' high, 7 chains East.

DIAGRAM

T17S	R27E
S2	S1
S11	S12

Description of corner evidence found:

16"x12"x10" Basalt stone 6" in ground with 5 faint notches on south, no marks remaining on east. No evidence of mound of stone found.
 Ravine course South 2 chains East, in place.
 Top of rocky bluff, 50' high, 7 chains East, in place.

Description of monument and accessories established to perpetuate the

original location of this corner: Set 2 1/2"x30" alum. pipe with 3" alum. cap marked: 22" in ground with mound of stone to cap, in place of of original stone.
 Buried original stone along SE side of pipe.
 15" Juniper N26 1/2°E 91.1', scribed "T17SR27ES1BT".
 13" Juniper N20 1/2°W 77.1', scribed "T17SR27ES2BT".
 14" Juniper S51°W 127.9', scribed "T17SR27ES11BT".
 15" Juniper S24 1/2°E 107.0', scribed "T17SR27ES12BT".
 Set 6' metal fence post 2.0' SE, with USFS 54-4 sign.
 BT's have USFS 54-3 and 54-4 signs, and 60d nail with 1 1/2" alum. disk marked "C. WAYNE COOK PLS 1098" in side center at base. Distance measured to nail with steel tape. Bearings measured with Silva Ranger compass (Var. 19° east).

T17S	R27E
S2	S1
S11	S12
1987	
PLS 1098	

I hereby certify that the above corner was perpetuated as hereon described on July 11, 1987.
 Witnessed by: C.G. Cook.

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

C. Wayne Cook

OREGON
 JULY 22, 1977
 C. WAYNE COOK
 1098

C. WAYNE COOK
 3180 ALDERCREST ROAD
 TILLAMOOK, OREGON 97141
 503-842-8380

Office of Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 12 day of Oct, 1987
Robert D. Baggett by _____
 (COUNTY OFFICIAL) (DEPUTY)