

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

G.L.O., 1882, by Henry W. Cooke, Contract #427.
Set pine post with marked stone 12" in ground.
Pits East and West at 5 1/2'.

DIAGRAM

T17S R27E
S 1
1/4 ———
S12

Description of corner evidence found:

No evidence of original corner found. Set at single proportionate position between section corners 1/2 mile East and 1/2 mile West.

SEE MAP OF SURVEY #1015

Description of monument and accessories I established to perpetuate the

original location of this corner:

Set 2"X30" alum pipe with 3" alum. cap, marked as shown, 29" in ground.
20" Ponderosa pine N52°E 49.6' scribed "1/4S1BT".
14" Juniper S68°E 43.9' scribed "1/4S12BT".
Set 6' metal fence posts 2.0' North and 1.5' South w/USFS 54-2 and 54-4 signs.
BT's have USFS 54-3 and 54-4 signs, and 60d nail with 1 1/2" alum. disk
"C. WAYNE COOK PLS 1098" in side center at base. Distance measured to
nail. Bearings measured with Silva Ranger compass (Var. 19° East). Corner
falls 23' West of old poorly maintained fence-line N20°WXS20°E.

T17S R27E
S 1
1/4 ———
S12
1987
PLS 1098

I hereby certify that the above corner was monumented as hereon described on
July 14, 1987.

Witnesses: L.R. Edgar, A.D. Cook and S.J. Everett.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

C. Wayne Cook

OREGON
JULY 22, 1977
C. WAYNE COOK
1098

C. WAYNE COOK
3180 ALDERCREST ROAD
TILLAMOOK, OREGON 97141
503-842-8380

Office of Surveyor County of Grant
State of Oregon I hereby certify that the within instrument was filed in this office
for record on the 12 day of Oct, 1987
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)