


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

G.L.O., 1882, by Henry W. Cooke, Contract #427.
Set 16"x12"x10" Basalt stone with mound of stone along side.



Description of corner evidence found:

No evidence of original corner found. Set at single proportionate distance between section corners 1/2 mile North and 1/2 mile south.

SEE MAP OF SURVEY # 1015.

Description of monument and accessories I established to perpetuate the

original location of this corner:

Set 2"x30" alum. pipe with 3" alum. cap, marked as shown, 24" in ground, with mound of stone to cap. Set 6' metal fence post N65°E 1.8' with USFS 54-4 sign. 8" Juniper S32°E 60.9' scribed "1/4S12BT". 9" Juniper S51 1/2°W 49.9' "1/4S11BT". BT's have USFS 54-3 and 54-4 signs, and 60d nail with 1 1/2" alum. disk "C. WAYNE COOK PLS 1098" in side center at base. Distance measured to nail. Bearings measured with Silva Ranger compass (Var. 19° East). Corner falls on an East slope 100' North of a prominent saddle in spur ridge course N35°W.	T17S R27E 1/4 S11 S12 1987 PLS 1098
---	---

I hereby certify that the above corner was monumented as hereon described on July 24, 1987.

Witnesses L.R. Edgar, C.G. Cook.

REGISTERED PROFESSIONAL LAND SURVEYOR

C. Wayne Cook

OREGON JULY 22, 1977 C. WAYNE COOK 1098
--

C. WAYNE COOK
3180 ALDERCREST ROAD
TILLAMOOK, OREGON 97141
503-842-8380

Office of Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 13 day of OCT, 1987
Robert D. Baggett by _____
 (COUNTY OFFICIAL) (DEPUTY)