

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

GLO, 1882, by Henry W. Cooke, contract #427.
Set 18"x14"x10" Basalt stone (no marks mentioned)
Mound of stone alongside.

DIAGRAM

T17S	R27E
S11	S12
S14	S13

Description of corner evidence found:

24"x14"x10" Basalt stone with 4 notches on south, 1 notch on east, and an "X" on south near top, set 4" in ground.
Remains of stone mound along north side of stone.

Description of monument and accessories I established to perpetuate the

original location of this corner: Set 2 1/2"x30" alum. pipe with 3" alum. cap marked: 20" in ground in place of original stone with mound of stone to cap.
Buried original stone in south portion of mound.
13" Juniper S36°E 126.8', scribed "T17SR27ES13BT".
16" Juniper S60°W 120.6', scribed "T17SR27ES14BT".
No BT's available in sections 11 or 12.
Set 6' metal fence post N37°W 3.7' with USFS 54-4 sign.
Set 6' metal fence post N70°E 2.8' with USFS 54-4 sign.
Corner is on open grassy south slope.
BT's have USFS 54-3 and 54-4 signs, and a 60d nail with a 1 1/2" alum. disk marked "C. WAYNE COOK PLS 1098" in side center at base. Distance measured to nail with a steel tape. Bearings measured with a Silva Ranger compass (Var. 19° east).

T17S	R27E
S11	S12
S14	S13
1987	
PLS 1098	

I hereby certify that the above corner was perpetuated as hereon described on July 21, 1987.
Witnessed by: C. G. Cook.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

C. Wayne Cook

OREGON
JULY 22, 1977
C. WAYNE COOK
1098

C. WAYNE COOK
3180 ALDERCREST ROAD
TILLAMOOK, OREGON 97141
503-842-8380

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 12 day of OCT, 1987
Robert D. Bugatt by _____
(COUNTY OFFICIAL) (DEPUTY)