

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

GLO, 1882, by Henry W. Cooke, contract #427
 Set 15"X12"X9" Basalt stone 10" in ground.
 28" Juniper N20°W 91 links (60.1')

DIAGRAM

T17S	R27E
S14	S13
S23	S24

Description of corner evidence found:

No stones of called size in vacinity, soil is very shallow (2"-3").
 28" Juniper N20°W 60.1' to face, face partially closed and badly weathered and burned, portions of scribe marks visible.

Description of monument and accessories I established to perpetuate the

original location of this corner: Set 2 1/2"X30" alum. pipe with 3" alum. cap marked: 18" in ground with mound of stone to cap, at record bearing and distance from original BT face.

11" Juniper S84°W 48.5', scribed "T17SR27ES23BT".

11" Juniper N74°W 32.5', scribed "T17SR27ES14BT".

10" Juniper N27°E 56.6', scribed "T17SR27ES13BT".

13" Juniper S77°E 17.5', scribed "T17SR27ES24BT".

Set 6' metal fence post 3.1' SE, with USFS 54-4 sign.

Corner is on steep east slope.

BT's have USFS 54-3 and 54-4 signs. New BT's have a 60d nail with a 1 1/2" alum. disk marked "C. WAYNE COOK PLS 1098" in side center at base. Distance measured to nail with steel tape. Bearings measured with Silva Ranger Compass (Var. 19° east).

I hereby certify that the above corner was perpetuated as hereon described on July 20, 1987.

Witnessed by: C. G. Cook.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

C. Wayne Cook

OREGON
JULY 22, 1977
C. WAYNE COOK
1098

C. WAYNE COOK
3180 ALDERCREST ROAD
TILLAMOOK, OREGON 97141
503-842-8380

Office of... *Surveyor* ... County of... *Grant* ...
 State of... *Oregon* ... I hereby certify that the within instrument was filed in this office
 for record on the... *12* day of... *Oct* ... 19... *87* ...
Robert D. Baggett by _____
 (COUNTY OFFICIAL) (DEPUTY)