


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

G.L.O., 1880, by Banford Robb, contract #366.
Set 10"X8"X8" Basalt stone in mound of stone.

G.L.O. 1882, retracement by Henry W. Cooke, contract #427,
Found as per original.



Description of corner evidence found:

No evidence of original corner found. Set at single proportionate position between the West 1/4 of section 6 and the West 1/4 of section 7.

SEE MAP OF SURVEY #1015

Description of monument and accessories established to perpetuate the

original location of this corner:


Set 2"X30" alum. pipe with 3" alum cap, marked as shown, 6" in ground with mound of stone to cap.

6" Juniper N68°E 96.0' scribed "T17SR28ES6BT".

No BT available in section 7

Set 6' metal fence post 3.4' North with USFS 54-4 sign.

BT has USFS 54-3 and 54-4 signs, and a 60d nail w/1 1/2" alum. disk "C. WAYNE COOK PLS 1098" in side center at base. Distance measured to nail. Bearing measured with Silva Ranger compass (Var. 19° East). Corner falls on a steep NW slope +/-75' North of a ridge top.



I hereby certify that the above corner point was monumented as hereon described on July 13, 1987.

Witnesses: L.R. Edgar, A.D. Cook and S.J. Everett.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

C. Wayne Cook

OREGON
JULY 22, 1977
C. WAYNE COOK
1098

C. WAYNE COOK
3180 ALDERCREST ROAD
TILLAMOOK, OREGON 97141
503-842-8380

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 13 day of Oct, 1987
Robert D. Dyer by _____
(COUNTY OFFICIAL) (DEPUTY)