


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

G.L.O., 1882, by Henry W. Cooke, Contract #427.
 Set Pine post and marked stone 12" in ground.
 Pits North and South at 5 1/2'.



Description of corner evidence found:

No evidence of original corner found. Reestablished at single proportionate distance between Section corners 1/2 mile North and 1/2 mile South. The line tree to the north was found up-rooted and out of position, therefore it was not used to proportion this corner.

SEE MAP OF SURVEY #1015

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2"X30" alum. pipe with 3" alum. cap, marked as shown, 28" in ground at proportionate position.
 16"X15" Double Juniper N42°W 16.5' scribed "1/4S8BT".
 14" Juniper N61°E 30.3' scribed "1/4S9BT".
 Set 6' metal fence post 1.8' West, w/ USFS 54-4 sign.
 BT's have USFS 54-3 and 54-4 signs, and a 60d nail w/ 1 1/2' alum. disk "C. WAYNE COOK PLS 1098" in side center at base. Distance measured to nail. Bearings measured with Silva Ranger compass (Var. 19° East).
 Corner falls 1.5' north of east-west fence line.

T17S R28E
 1/4
 S8 | S9
 1987
 PLS 1098

I hereby certify that the above corner point was monumented as hereon described on July 10, 1987.
 Witnesses: L.R. Edgar, A.D. Cook and S.J. Everett.

**REGISTERED
 PROFESSIONAL
 LAND SURVEYOR**

C. Wayne Cook

**OREGON
 JULY 22, 1977
 C. WAYNE COOK
 1098**

**C. WAYNE COOK
 3180 ALDERCREST ROAD
 TILLAMOOK, OREGON 97141
 503-842-8380**

Office of Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 17 day of Oct, 1987
Robert D. Edgar (COUNTY OFFICIAL) C. Wayne Cook (DEPUTY)