


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

GLO, by Henry W. Cooke, 1882, Contract #427
 Set 16"x12"x20" stone with 4 notches on East and South sides.
 Pits in each section at 5 1/2'.




Description of corner evidence found:

18"x12"x10" stone with 4 bold notches on East and 4 faint notches on South, set in ground.
 No evidence of pits remaining.

Description of monument and accessories established to perpetuate the

original location of this corner: Set 2 1/2"x30" alum. pipe with 3"alum. cap marked: 28" in ground in place of original stone, with original stone buried along South side of pipe.
 14" Juniper N64°W 122.9', scribed "T17SR28ES8BT".
 16" Juniper N58°E 135.7', scribed "T17SR28ES9BT".
 14" Juniper S64°E 47.9', scribed "T17SR28ES16BT".
 21" Juniper S19°W 114.3', scribed "T17SR28ES17BT".
 Set 6' metal fence post 1.9' South with USFS 54-4 sign.
 Corner is on north side of shallow draw course S70°E.
 BT's have USFS 54-3 and 54-4 signs, and 60d nail with 1 1/2" alum. disk marked "C. WAYNE COOK PLS 1098" in side center at base. Distance measured to nail with steel tape. Bearings measured with Silva Ranger compass (Var. 19° east).



I hereby certify that the above corner was perpetuated as described hereon on July 10, 1987.

Witnessed by: L.R. Edgar, A.D. Cook and S.J. Everett.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

C. Wayne Cook

**OREGON
JULY 22, 1977
C. WAYNE COOK
1098**

**C. WAYNE COOK
3180 ALDERCREST ROAD
TILLAMOOK, OREGON 97141
503-842-8380**

Office of Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 12 day of Oct, 1987
Robert D. Bequest by _____
 (COUNTY OFFICIAL) (DEPUTY)