


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**History of original corner establishment:**

GLO, 1882, by Henry W. Cooke, contract #427.  
Set 14"x10"x8" Basalt stone 11" in ground with "1/4" on west.  
Pits North and South at 5 1/2'.  
Top of ridge course NW X SE called at same chainage as corner  
(40.00 chains).



**Description of corner evidence found:**

14"x11"x9" Basalt stone broken into several pieces, set 8" in ground, with faint  
"1/4" visible on one piece.  
No evidence of pits remaining.  
Ridge top course NW X SE 26' North.

**Description of monument and accessories | established to perpetuate the**

<b>original location of this corner:</b> Set 2 1/2"x30" alum. pipe with 3" alum. cap marked: 17" in ground in place of original stone with mound of stone to cap. Buried peices of original stone in south portion of mound. No BT's available. Set 6' metal fence post 2.6' South with USFS 54-4 and 54-5 signs. Set 6' metal fence post 2.9' West with USFS 54-4 and 54-5 signs.	T17S R28E 1/4 S15   S14 1987 PLS 1098
---	---

I hereby certify that the above corner was perpetuated as hereon described on  
July 26, 1987.  
Witnessed by: C.G. Cook and S.J. Everett.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*C. Wayne Cook*

OREGON  
JULY 22, 1977  
C. WAYNE COOK  
1098

C. WAYNE COOK  
3180 ALDERCREST ROAD  
TILLAMOOK, OREGON 97141  
503-842-8380

Office of SURVEYOR County of Grant  
State of Oregon, I hereby certify that the within instrument was filed in this office  
for record on the 12 day of OCT, 1987  
Robert D. Bissett by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)