


CORNER RESTORATION

CORNER: SE Cor. Sec. 27 Twp. 17 S. Range 28 E., W.M.

ORIGINAL SURVEY BY: Henry W. Cooke

CONTRACT NUMBER: 427

CONTRACT DATE: December 18, 1881



ORIGINAL DESCRIPTION: Set a basalt stone 18x6x6 ins 12 ins in ground for 1/4 Cor to secs 26, 27, 34 & 35 marked with 1 notch on South and 2 notches on East sides and raised a mound of stone 2 ft high 4½ ft base alongside.
NOTE: Cooke's field notes state "... for 1/4 Cor to secs 26, 27, 34 & 35. ..." I assume the "1/4 Cor" should have read "Cor".

RESTORATION BY, STAMP AND DATE:

Michael C. Springer, PLS
Jason L. Hatfield, PLS

RECEIVED AND FILED

August 18, 2010

OFFICE OF COUNTY SURVEYOR

[Signature]
ATTEST: *[Signature]*

REGISTERED PROFESSIONAL LAND SURVEYOR

[Signature]
OREGON
JULY 9, 2002
MICHAEL C. SPRINGER
#70918

EXPIRES: 6/30/2012

July 27, 2010

Grant County Surveyor

EVIDENCE FOUND: Found stone 16"x5"x4" lying loosely with other stones, marked with 1 groove on the South face and 2 grooves on the East face. The stone was completely buried with the South face up. From the found stone we found an 11" DBH juniper N.23°E., 18.4 feet distant and an 18" DBH juniper S.02°E., 18.15 feet distant with U.S. Forest Service BT tag attached. I accept the position of the found marked stone for the Section Corner

DESCRIPTION OF MONUMENTS AND ACCESSORIES SET AND METHODS USED:

At the corner point I set a 1½"x30" galvanized iron pipe with attached Grant County Surveyor Brass cap, 28" in the ground with a 3 ft. mound of stone. We buried the original marked stone North and alongside the new monument. Cap is marked as shown hereon.

FROM WHICH I MARK THE FOLLOWING BEARING TREES:

A juniper 11 inch diam. bears N.23°E., 18.40 feet, marked "T17SR28ES26 CSBT"

A juniper 18 inch diam bears S.02°E., 18.15 feet, marked "T17SR28ES35 CSBT"

A mahogany, with multiple trunks, the 6 inch diam South trunk bears N.09°W., 47.55 feet, marked "S27 BT"

ALSO FROM WHICH I SET THE FOLLOWING NEW REFERENCE POINT:

A 5/8"x30" iron pin, bears S.72°W., 31.37 ft., with attached 1½" aluminum cap marked "GRANT COUNTY SURVEYOR RPI 2010".

We used a magnetic compass with 17° variance and a steel tape to measure to a 50d nail in the side-center of the root crown of the BT's. Used RTK GPS to measure to the RP.

STATE PLANE COORDINATES: (3601 OR N)

Reference Datum: WGS84
Northing: 146,241.1 ft.
Easting: 8,507,957.8 ft.
Ellip Ht: 4,789.0 ft.

