

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


INDEX No. A-7

History of original corner establishment:

Corner was originally established by Bamford Robb, in Aug., 1880, under General Land Office Contract No. 366. The U.S. Surveyor Generals Notes State: Set post for 1/4 sec. cor.

from which:

A pine 36 in dia. bears N20°W., 28 lks dist.
" " 30 " " " S10°E., 154 " "



Description of corner evidence found:

No trace of the original post is remaining.

Found the North Bearing Tree, which is a 40" Pine with blaze and scribe reading "1/4"
Found the South Bearing Tree, which is a 36" Pine with blaze and scribing visible.
Set the 1/4 corner position at the intersection of the record distances from the blaze face of the above described original bearing trees.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 24" in the ground and raised a mound of earth around the pipe.
From Which:
(New Bearing Trees)
A Pine 8" dia., Bears N 5°E., 44.6 ft., scribed: 1/4 S32 BT
A Pine 10" dia., Bears S13°E., 91.8 ft., scribed: 1/4 S5 BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, 5 ft. South & West from the Corner.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

**OREGON
JULY 12, 1989
DOUGLAS M. FERGUSON
848**

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: June 4, 1987
Refer to Map of Survey No. 1004

Office of Sidney County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 3 day of Oct, 1987
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)