

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. E-9


**History of original corner establishment:**

Corner was originally established by Bamford Robb, in Aug, 1880, under General Land Office Contract No. 366. The U.S. Surveyor Generals Notes State:

Set Stone 22x10x10 in mound of stone for cor to secs. 4-5-8 & 9

from which:

A pine 14 in dia. bears S24<sup>0</sup>W., 78 lks dist.



**Description of corner evidence found:**

No trace of the (22"x10"x10") stone is found.

Found the only bearing tree originally established, which is a 34" Pine with scribing visible.

Set corner position at record measurement from the blaze face of this said Pine Tree.


**Description of monument and accessories | established to perpetuate the original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 26" in the ground.

From Which:

- A Pine 14" dia., Bears N50<sup>0</sup>W., 23.3 ft., scribed: T17S R29E S5 BT
  - A Pine 24" dia., Bears N30<sup>0</sup>E., 20.3 ft., scribed: T17S R29E S4 BT
  - A Fir 20" dia., Bears S 7<sup>0</sup>E., 41.7 ft., scribed: T17S R29E S9 BT
  - A Pine 16" dia., Bears S50<sup>0</sup>W., 11.0 ft., scribed: T17S R29E S8 BT
- Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence post with warning Sign, North 3 ft. from the corner.



This work is performed by:  
Douglas M. Ferguson RLS 848  
Mt. Vernon Oregon.  
On: June 4, 1987  
Refer to Map of Survey No. 1004

Office of Surveyor County of Grant  
State of Oregon, I hereby certify that the within instrument was filed in this office  
for record on the 2 day of Oct, 1987  
Court E. B. Smith by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)