


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. P-5

History of original corner establishment:

Corner was originally established by Bamford Robb, in Aug, 1880, under General Land Office Contract No. 366. The U.S. Surveyor Generals Notes State: Set stone 16x12x8 in mound of stone for 1/4 sec. cor.



from which:

A Pine 14 in dia., bears N12°W., 20 lks. dist.

Description of corner evidence found:

Found a 18"x12"x7 stone lying flat on the ground, with "1/4" visible near the top.

Found a dead and down 20" Pine with scribing visible but unreadable, which bears record measurement from the above described stone.

Accepted the above described stone as the 1/4 sec. cor

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 26" in the ground and set the original stone North alongside the pipe.


From Which:

A Pine 11" dia., Bears N65°E., 26.1 ft., scribed: 1/4 S20 BT

A Pine 14" dia., Bears S29°W., 22.0 ft., scribed: 1/4 S19 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence post with warning Sign, North 3 ft. from the corner.



This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: May 20, 1987
Refer to Map of Survey No. 1004

Office of..... *Burman* County of..... *Grant*
State of..... *Oregon* I hereby certify that the within instrument was filed in this office
for record on the..... *2* day of..... *Oct* 19..... *87*
Count D. Baggett by
(COUNTY OFFICIAL) (DEPUTY)