

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: *

The original corner was established in 1880 by Bamford Robb under Contract No. 366 dated August 18, 1880. The original notes state:

DIAGRAM
T17S R29E
1/4
S301S29

Set stone 16x14x6 in mound of stone for 1/4 sec cor from which
A pine 36 ins dia bears S 48° E 31 lks dist.

Description of corner evidence found:

Found no evidence of the original monument.
A 32" P.Pine bears S48°E, 20.5 ft (S48°E, 31 lks) to face, 4S (backwards S) in an opened face.

Description of monument and accessories I establish to perpetuate the original location of this corner:

At record distance and direction from the original bearing tree, I set a 2 1/2" x 28" aluminum monument 22" in the ground in a small mound of stone.

T17S R29E
1/4
S301S29
PLS1918
1988

I establish new bearing trees:

An 11" P.Pine bears S44 1/2°E, 14.2 ft, scribed 1/4S29BT.
A 10" P.Pine bears S58-3/4°W, 23.6 ft, scribed 1/4S30BT.

New BTs have 3/4" brass washers marked PLS1918 attached to the BT blaze, faces and bands painted with red tree marking paint, and BT tags and Attention or Land Survey Monument signs. A steel fence post with Attention or Land Survey Monument sign is driven approximately 3-5 feet from the corner.

Smokey Cadastral Survey, Cont. No. 53-04H1-7-4011

Field Book: FB 3-44

Work accomplished: 6/19/88


Witnesses: Tyler Parsons

Louise Parsons

Sharon Parsons

Job No.: 87226

PARSONS SURVEYING
1915 S.E. Stone Street
Corvallis, OR 97333
(503) 752-7515



Office of COUNTY SURVEYOR

County of GRANT

State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 4 day of Nov, 19 88

Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)