

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

The original corner was established in 1880 by Bamford Robb under Contract No. 366 dated August 18, 1880. The original notes state:

Set basalt stone 16x12x8 in mound of stone for cor to secs 25-36-30&31.

DIAGRAM  
T17S  
R28E R29E  
S25|S30  
----+----  
S36|S31

Description of corner evidence found:

Found no evidence of the original corner monument.

Description of monument and accessories I establish to perpetuate the original location of this corner:

I reestablish this corner by single proportion. Set a 2 1/2 x 28" aluminum monument 24" in the ground.

I establish new bearing trees:

A 1 1/2" aluminum cap on rebar bears N60°23'E, 14.9 ft, marked RP S30 14.9FT PLS1918.

A 17" P.Pine bears N 51 1/4°W, 236.0 ft, scribed T17SR28ES25BT. No other suitable trees in range.

T17S  
R28E R29E  
S25|S30  
----+----  
S36|S31  
PLS1918  
1988

New BTs have 3/4" brass washers marked PLS1918 attached to the BT blaze, faces and bands painted with red tree marking paint, and BT tags and Attention or Land Survey Monument signs. A steel fence post with Attention or Land Survey Monument sign is driven approximately 3-5 feet from the corner.

Smokey Cadastral Survey, Cont. No. 53-04H1-7-4011


Field Book: FB 3-25 & 4-1

Work accomplished: 6/21/88

Witnesses: Douglas Parsons  
Tyler Parsons

Job No.: 87226

PARSONS SURVEYING  
1915 S.E. Stone Street  
Corvallis, OR 97333  
(503) 752-7515



Office of COUNTY SURVEYOR

County of GRANT

State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 4 day of Nov, 19 88

Robert D. Buzette by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)