

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**History of original corner establishment:**

Corner was established by Bamford Robb, US Deputy Surveyor, during the original survey Joint Contract No. 357 dated July, 1880.

Set post for 1/4 Sec. cor with pits and mound as per instruction

**DIAGRAM**

T16S R30E

S36  
1/4 ---  
S 1  
T17S  
1986  
PLS 699

**Description of corner evidence found:**

The corner falls in the vicinity of a gate through the E-W fence. A lot of animal and vehicle activity has blotted out any corner evidence.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 24" in the ground to rock, at single proportionate measurements from adjacent found corners and using found line trees for alignment control. Built a mound of earth & rock to be 30" in diameter by 6" high around the monument, from which new BTs are:


14" Ponderosa pine bears N53°E, 142.2 feet scribed 1/4 S36 BT

16" Ponderosa pine bears S43°E, 76.0 feet scribed 1/4 S1 BT


Attached BT and Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation, to stamped aluminum washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet W and 35 feet E of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and an Attention sign to the W post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on April 30, 1986, I re-established the corner as herein described.



*Leland L. Myers*



**FILED**

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 6 DAY OF June, 1986

*Robert D. Baggett*  
Grant County Surveyor