

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by A. O. Eckelson, US Deputy Surveyor, during the original survey Joint Contract No. 366 dated August, 1880.

Set stone 16x10x8 in mound of stone for cor to secs 1, 2, 11 & 12 from which

A pine 30 ins diam bears N50°W, (22.4') 34 lks dist

A pine 24 ins diam bears N76°E, (37.0') 56 lks dist

DIAGRAM

T17S R30E

S 2	S 1
S11	S12

1986
PLS 699

Description of corner evidence found:

16x8x5 stone with 2 notches on E face, 5 notches on S and "X" on up side in a mound of rocks. The corner is in a skid road, but fortunately small trees pushed over by the skid cat protected the corner stone.

36" Ponderosa pine (Down & Rotting Away) (Scribing Visible) (1880 BT) bears as best could be determined N50°W, 22.4 feet. The remains of the BT are about 15' NW of it's true location.

24" pine (1880 BT) not found.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 22" in the ground to rock, replacing the rock which is turned upside down and buried on the north side of the monument. Improved the existing mound with rock & earth to be 30" in diameter by 8" high around the monument, from which new BTs are:

9" Douglas-fir bears S34° 30'W, 25.0 feet scribed T17SR30E S11 BT

7" Douglas-fir bears N69°W, 16.2 feet scribed T17SR30E S2 BT

12" Douglas-fir bears N31°E, 18.4 feet scribed T17SR30E S1 BT

11" Douglas-fir bears S24° 15'E, 32.7 feet scribed T17SR30E S12 BT

Attached BT and Attention signs to and painted a red band around each BT. Bearings were taken with a staff compass, using a declination of 18° 30'E, to stamped brass washers nailed in the scribed red-painted blazes.

Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set a steel fence post 5 feet S of the corner with an Attention sign attached. The monument is not a National Forest property corner.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on June 1, 1986, I monumented the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF Sept, 1986

Leland L. Myers
Grant County Surveyor

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Leland L. Myers
OREGON
JULY 9, 1965
LELAND LEE MYERS
699