

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by S. W. Lackland, US Deputy Surveyor, during the original survey Contract No. 384 dated March, 1881.

Set post for corner to Townships 16 & 17 South Ranges 30 & 31 East from which

- A pine 24 ins diam bears S85°E, (9.2')14 lks dist
- A pine 36 ins diam bears N85°E, (18.5')28 lks dist
- A pine 28 ins diam bears N70°W, (49.5')75 lks dist
- A pine 30 ins diam bears S10°W, (67.3')102 lks dist

DIAGRAM

T16S
R30E | R31E
S36 | S31
S 1 | S 6
T17S
PLS 699

Description of corner evidence found:

Found some evidence of at least 3 pits after measuring in from the BTs. Ground fire has burned any other evidence.

- 31" Ponderosa pine (Good Condition)(Scribing Visible)(1881 BT) bears S79° 30'E, 10.4 feet.
- 36" Ponderosa pine (Good Condition)(Scribing Visible)(1881 BT) bears N85° 15'E, 20.0 feet.
- 33" Ponderosa pine (Good Condition)(Scribing Visible)(1881 BT) bears N71°W, 51.2 feet.
- 30" Ponderosa pine (40' Broken Stub)(Scribing Visible)(1881 BT) bears S9° 30'W, 68.6 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 26" in the ground, at the point determined by the bearing trees. Built a mound of rock & earth to be 24" in diameter by 4" high around the monument, from which a new BT is:

15" Ponderosa pine bears S34°W, 59.9 feet scribed T17SR30E S1 BT

Attached BT and Attention signs to and painted a red band around each BT. Bearings were taken with a staff compass, using a declination of 18° 30'E, to stamped aluminum washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 3 feet S and 5 feet W of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and an Attention sign to the S post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on March 4, 1986, I monumented the corner as herein described.

FILED

IN THE OFFICE OF THE GRANT COUNTY SURVEYOR

THIS 6 DAY OF June, 1986

Roland D. Begett
Grant County Surveyor

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Leland L. Myers

OREGON
JULY 9, 1965
LELAND LEE MYERS
699