

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by S. W. Lackland, US Deputy Surveyor, during the original survey Contract No. 384 dated March, 1881.

Set stone 16x8x5 in mound of stone for 1/4 sec cor from which

A pine 26 ins diam bears S67°E, (83.8') 127 lks dist

DIAGRAM

T17S R31E

1/4
S 3 | S 2

1986
PLS 699

Description of corner evidence found:

16x9x5 rock laying face down about 3' down the hill from the remenants of a rock mound. Corner is on a very steep and loose shale-like rock hillside.

40" Ponderosa pine (Good Condition) (Blaze Opened by Others) (1881 BT) bears S45° 30'E, 79.1 feet feet. No scribing was visible even though the blaze had been chopped-out at one time.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3/4" aluminum cap, marked as shown in the diagram, 26" in the ground, replacing the rock which is turned upside down and buried on the north side of the monument. Improved the existing mound with rock & earth to be 30" in diameter by 4" high around the monument.


No new bearing trees set because No trees were available in Section 3.

30" No. 5 rebar with 2" aluminum cap Reference Monument bears N3°E, 16.2 feet stamped RN 16.2' ↓ 1986 PLS 699


Attached BT and Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet N and 5 feet S of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and an Attention sign to the N post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on October 28, 1986, I monumented the corner as herein described.



Leland L. Myers



FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 6 DAY OF April, 1987

Robert D. Baggett
Grant County Surveyor