

RECORD OF LAND CORNER MONUMENTATION


CORNER: N $\frac{1}{4}$ Cor. Sec. 11, T.17S., R.31E., W.M.

ORIGINAL SURVEY BY: Rueben R. Leigh

CONTRACT NUMBER: 489

CONTRACT DATE: August 15, 1883

SUBSEQUENT SURVEY: Scott R. McIntyre 1979



ORIGINAL G.L.O. DESCRIPTION: Set a basalt stone 14x12x10 ins. 9 ins. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face from which: A pine 15 ins. dia. bears S.42°E., 34 lks dist. marked $\frac{1}{4}$ S BT. A pine 36 ins. dia. bears N.23°E., 53 lks. dist. marked $\frac{1}{4}$ S BT.

1979 RESURVEY BY SCOTT R. MCINTYRE, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 05/21/1979 (Pg. 376): SEE RECORD MAP OF SURVEY NO. 752.

The $\frac{1}{4}$ sec. cor. of secs. 2 and 11, determined at record bearing and distance from the remains of the original bearing trees:

A decayed pine stump, 36 ins. diam., bears N. 23° E., 53 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on partially healed blaze.

A pine, 17 ins. diam., bears S. 42° E., 34 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 17 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 17 S R 31 E
 $\frac{1}{4}$ S 2
S 11
1979

from which a new bearing tree

A fir, 10 ins. diam., bears N. 49° W., 31 lks. dist., mkd. $\frac{1}{4}$ S2 BT.

EVIDENCE FOUND:

None. No field visit was made for this Corner Restoration Report, it has been prepared from record General Land Office and Bureau of Land Management field notes. See Record Map of Survey 752 filed in the Grant County Surveyor's Office.

PREPARED BY:

Michael C. Springer, PLS
Grant County Surveyor
Marcus Teague, Technician

217 N. Canyon Blvd.
John Day, OR, 97845
(541) 575-1251

December 21, 2016

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

DEC 27 2016

BY: 

REGISTERED
PROFESSIONAL
LAND SURVEYOR


OREGON
JULY 9 2002
MICHAEL C. SPRINGER
#70918

EXPIRES: 6/30/2018