

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. E-23

History of original corner establishment:

This corner was established by Henry W. Cooke, in 1883, under GLO Contract No. 488. Surveyor General Notes state:

Set stone 14x12x10 ins. 10 in. deep marked 1/4 on N. face. Raised a mound of stone alongside.

DIAGRAM

T17S R31E
S 1

S12
1992
PLS 848

Description of Corner Evidence Found:

Found original stone in place clearly marked 1/4.

Description of monument and accessories I established to perpetuate the original location of this corner:

I moved the original corner stone aside and in it's place I set a 2-1/2"x30" aluminum pipe with 3-1/4" aluminum cap, stamped as shown on the DIAGRAM, 8" in the ground and raised a mound of stone alongside the monument. Buried the original stone on the north side of the monument.

From Which:

Ponderosa Pine, 22" dia., bears N63°30'W, 78.1 ft., scribed: 1/4 S1 BT
Ponderosa Pine, 8" dia., bears N47°45'E, 63.9 ft., scribed: 1/4 S1 BT
Ponderosa Pine, 10" dia., bears S29°00'E, 171.0 ft., scribed: 1/4 S12 BT
Ponderosa Pine, 20" dia., bears S26°15'W, 120.2 ft., scribed: 1/4 S12 BT

Measurements to BT's taken with a magnetic compass, declination 20° East, and a nylon clad steel tape. Set steel fence post with Land Survey Monument (54-9) sign 5' north of the monument. Nailed a brass washer stamped PLS 848 on blaze above BT scribe as taken this survey. Nailed Bearing Tree (54-3) signs above blaze and Land Survey Monument (54-9) signs on back of each tree as required. Painted a 6" red band above Bearing Trees signs and painted blaze red.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1908
DOUGLAS M. FERGUSON
848

This work was performed by:
Douglas M. Ferguson PLS 848
Witnessed by: D. Mitchell Ferguson
and Rick Saul
May 20, 1992
Refer to Grant Co. Survey No.: 1218

Office of Surveyor County of Grant
State of OR I hereby certify that the within instrument was
filed in this office for record on the 16 day of Oct, 1992
Robert D. Bayart by _____
(COUNTY OFFICIAL) (DEPUTY)