

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner has not been previously set.

DIAGRAM

T17S R31E

NE1/16+S10

1986
PLS 699

Description of corner evidence found:

Corner is being set by this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 24" in the ground to rock, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. Built a mound of rock & earth to be 30" in diameter by 6" high around the monument, from which new BTs are:

16" Douglas-fir bears N41° 30'W, 13.5 feet scribed NE1/16 S10 BT

14" Ponderosa pine bears S44° 45'W, 9.6 feet scribed NE1/16 S10 BT

Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground. Set steel fence posts 5 feet E and 5 feet S of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and a Land Survey Monument sign to the E post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 15, 1986, I established the corner as herein described.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 6 DAY OF April, 1987

Leland L. Myers
Grant County Surveyor