

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by S. W. Lackland, US Deputy Surveyor, during the original survey Contract No. 384 dated March, 1881.

Set stone 24x14x14 in mound of stone for cor to secs 7, 8, 17 & 18 from which

A pine 30 ins diam bears S24°W, (52.8') 180 lks dist

A pine 26 ins diam bears N46°W, (50.2') 76 lks dist

DIAGRAM

T17S R31E

S 7	S 8
S18	S17

1986
PLS 699

Description of corner evidence found:

19x12x8 stone with chisel marks badly weathered and chipped. The stone was laying down with the top to the East and the mound is to the South of the stone.

Root Collar (1881 BT) bears S24°W, 52.8 feet. Appears to be the last remains of the bearing tree.

18" Ponderosa pine (Burned Snag) (Scribing Visible) (1881 BT) bears N42° 30'W, 51.2 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 24" in the ground to hard pan, replacing the rock which is turned upside down and buried on the north side of the monument. Improved the existing mound with rock & earth to be 32" in diameter by 6" high around the monument, from which new BTs are:

7" Ponderosa pine bears N34° 30'W, 50.6 feet scribed T17SR31E S7 BT

5" Ponderosa pine bears N56°E, 3.2 feet scribed T17SR31E S8 BT

11" Ponderosa pine bears S22° 30' E, 23.2 feet scribed T17SR31E S17 BT

7" Ponderosa pine bears S61° 45'W, 24.8 feet scribed T17SR31E S18 BT

Attached BT and Attention signs to and painted a red band around each BT. Bearings were taken with a staff compass, using a declination of 18° 30'E, to stamped aluminum washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet W and 5 feet E of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and an Attention sign to the W post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on March 18, 1986, I monumented the corner as herein described.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 6 DAY OF June, 1986

Robert D. Sargent
Grant County Surveyor