

RECORD OF LAND CORNER MONUMENTATION


CORNER: NE Cor. Sec. 15, T.17S., R.31E., W.M.

ORIGINAL SURVEY BY: Samuel L. Lackland

CONTRACT NUMBER: 197

CONTRACT DATE: May 29, 1881

SUBSEQUENT SURVEYS: Scott R. McIntyre 1979, Phillip G. Griffin 1986



ORIGINAL G.L.O. DESCRIPTION: Set stone 21x14x12 in mound of stone for cor. to secs. 10, 11, 14, & 15. From which: A pine 40 in. dia. bears S.27°W., 25 lks. dist. A Pine 20 in. dia. bears S10°E., 38 lks dist.

1979 RESURVEY BY SCOTT R. MCINTYRE, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 05/21/1979 (Pg 371-372): SEE RECORD MAP OF SURVEY NO. 752.

The cor. of secs. 10, 11, 14, and 15, monumented with an embedded mound of stone, 2 ft. base, 6 ins. high, from which the remains of the original bearing trees:

A root hole, bears S. 10° E., 38 lks. dist., with a down pine alongside, 20 ins. diam., with scribe marks T17S R31E S14 BT visible on partially healed blaze.

A decayed pine stump, size indeterminate, bears S. 27° W., 25 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T 17 S R 31 E
S 10 | S 11
S 15 | S 14
1979

from which new bearing trees

A fir, 12 ins. diam., bears N. 72° E., 77 lks. dist., mkd. T17S R31E S11 BT.

A pine, 9 ins. diam., bears S. 45° E., 52½ lks. dist., mkd. T17S R31E S14 BT.

A pine, 10 ins. diam., bears S. 20° W., 63 lks. dist., mkd. T17S R31E S15 BT.

A fir, 10 ins. diam., bears N. 5° W., 35 lks. dist., mkd. T17S R31E S10 BT.

1986 RESURVEY BY PHILLIP G. GRIFFIN, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 07/08/1986 (Pg. 345):

From the cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, in a collar of stone, 2½ ft. base, to top, with brass cap mkd.

T 17 S R 31 E
S 10 | S 11
S 15 | S 14
1979

from which the remains of the original bearing trees

A root hole, bears S. 10° E., 38 lks. dist., with a pine log alongside, 20 ins. diam., with scribe marks S14 T17 S31 BT visible on open blaze.

A decayed pine stump, size indeterminate, bears S. 30° W., 27 lks. dist., no marks visible. (Record, S. 27° W., record and to face, 25 lks.)

and bearing trees mkd. by McIntyre

A fir, 13 ins. diam., bears N. 69½° E., 76 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, N. 72° E., 77 lks.)

A ponderosa pine, 12 ins. diam., bears S. 45° E., 52½ lks. dist., with fragmentary scribe marks visible on pitched over blaze.

A ponderosa pine, 11 ins. diam., bears S. 20° W., 63 lks. dist., with fragmentary scribe marks visible on pitched over blaze.

A fir, 11 ins. diam., bears N. 5° W., 35 lks. dist., with fragmentary scribe marks visible on pitched over blaze.

EVIDENCE FOUND:

None. No field visit was made for this Corner Restoration Report, it has been prepared from record General Land Office and Bureau of Land Management field notes. See Record Map of Survey 752 filed in the Grant County Surveyor's Office.

PREPARED BY:


Michael C. Springer, PLS
Grant County Surveyor
Marcus Teague, Technician

217 N. Canyon Blvd.
John Day, OR, 97845
(541) 575-1251

December 20, 2016

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

DEC 27 2016

BY: 

REGISTERED
PROFESSIONAL
LAND SURVEYOR


OREGON
JULY 9, 2002
MICHAEL C. SPRINGER
#70918

EXPIRES: 6/30/2018