

RECORD OF LAND CORNER MONUMENTATION


CORNER: N $\frac{1}{4}$ Cor. Sec. 13, T.17S., R.31E., W.M.

ORIGINAL SURVEY BY: Rueben R. Leigh

CONTRACT NUMBER: 489

CONTRACT DATE: August 15, 1883

SUBSEQUENT SURVEY: Scott R. McIntyre 1979



ORIGINAL G.L.O. DESCRIPTION: Set basalt stone 14x10x8 ins. 9 ins. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face from which: A pine 40 ins. dia. bears N36°E., 160 lks. dist. marked $\frac{1}{4}$ S BT. No other trees within limits and raised a mound of stone alongside.

1979 RESURVEY BY SCOTT R. MCINTYRE, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 05/21/1979 (Pg 361): SEE RECORD MAP OF SURVEY NO. 752.

The $\frac{1}{4}$ sec. cor. of secs. 12 and 13, determined at record bearing and distance from the remaining original bearing tree:

A pine, 43 ins. diam., bears N. 36° E., 160 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground, to solid rock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T 17 S R 31 E
 $\frac{1}{4}$ S 12
S 13
1979

from which a new bearing tree

A pine, 7 ins. diam., bears S. 57° W., 110 lks. dist., mkd. $\frac{1}{4}$ S13 BT.

EVIDENCE FOUND:

None. No field visit was made for this Corner Restoration Report, it has been prepared from record General Land Office and Bureau of Land Management field notes. See Record Map of Survey 752 filed in the Grant County Surveyor's Office.

PREPARED BY:

Michael C. Springer, PLS
Grant County Surveyor
Marcus Teague, Technician

217 N. Canyon Blvd.
John Day, OR, 97845
(541) 575-1251

December 23, 2016

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

DEC 27 2016

BY: 

REGISTERED
PROFESSIONAL
LAND SURVEYOR


OREGON
JULY 9, 2002
MICHAEL C. SPRINGER
#70918

EXPIRES: 6/30/2018