

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner has not been previously set.

DIAGRAM

T17S R31E

SW1/16+S16

1986
PLS 699

Description of corner evidence found:

Corner is being set by this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 36" in the ground to place the cap 6" below the surface on the N shoulder of the road, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. Ties checked and/or Accessories found, from which new BTs are:

8" Ponderosa pine bears S17° 45'E, 37.0 feet scribed SW1/16 S16 BT

11" Ponderosa pine bears N55° 45'E, 20.2 feet scribed SW1/16 S16 BT

Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground. Set steel fence posts 5 feet N and 60 feet W of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and a Land Survey Monument sign to the N post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 17, 1986, I established the corner as herein described.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 6 DAY OF Apr, 1987

Robert O. Bays
Grant County Surveyor